


# Material Safety Data Sheet Luxcare Paint Protector & Renewer



#### **Section 1 - Material Identification and Use**

Manufacturer's NameCal-Tex Protective Coatings, IncorporatedManufacturer's Address7455 Natural Bridge Caverns RoadSchertzTX78154Emergency Phone NumberINFOTRAC1-800-535-505324 Hours Per Day, 7 Days Per WeekSupplier Name and IdentifierCal-Tex Protective Coatings, IncorporatedSupplier's Address7455 Natural Bridge Caverns RoadSchertzTX78154MSDS Prepared ByRonnie L. Meadows(210) 564-3200Trade NameLuxcare Paint Protector & RenewerProduct UseAuto Paint Sealant Protector


### **Section 2 - Hazardous Ingredients of Material**

No.	Chemical Identity	Concentration	CAS	PEL	TLV	STEL	IDLH
2	Solvent Naphtha (Petroleum) Medium Aliphatic	Trade Secret	64742-88-7	100	100	N/A	
4		Trade Secret					
5	Organic Emulsion	Trade Secret	Mixture				
6	Poly (Dimethylsiloxane)	Trade Secret	63148-62-9				

NA = Not Applicable ND = No Data Available < = Less Than > = More Than Ceiling Value \*\* Chemical Believed to be a Potential Carcinogen (NIOSH) **Section 3 - Hazardous Identification** WHMIS Warning: FYF This chemical may affect the eye or visual capacity SKIN **~** This chemical may affect the dermal layer of the body LUNGS **~** This chemical may irritate or damage pulmonary tissue **NERVOUS SYSTEM** This chemical may produce a toxic affect on the nervous system REPRODUCTIVE May affect reproductive capabilities including mutations and effects on the fetus. **BLOOD** This chemical may act on the blood or hematopoietic system; decrease hemoglobin function; deprive tissue of oxygen **I IVFR** This chemical may produce liver damage - Hepatotoxins **KIDNEYS** This chemical may produce kidney damage - Neprotoins

#### **Section 4 - First Aid Measures**


INGESTION	<b>V</b>	DO NOT induce vomiting. Rinse mouth with water and give plenty of milk. Never give liquids to an unconcious victim - Seek Immediate Medical Attentio
EYE CONTACT	<b>✓</b>	Flush immediately with plenty of water for at least 15 minutes - Seek Medical Attention
SKIN CONTACT	_	Wash thoroughly with soap and water - Seek Medical Attention if irritation persists
INHALATION	<b>✓</b>	Remove to fresh air. If breathing is difficult give oxygen - If not breathing give artificial respiration -Get Medical Attention
SPECIAL		None Identified




# Material Safety Data Sheet Luxcare Paint Protector & Renewer



#### Special Info **Section 5 - Fire-Fighting Measures** Carbon dioxide, dry chemical, water fog, water **Extinguishing Media** Upper Explosion Limit Not Determined Flashpoint F N/A spray, foam. Lower Explosion Limit Not Determined N/A Flashpoint C **DO NOT USE WATER** Auto-Ignition Temp. Not Determined Use self contained breathing apparatus when fighting large fires. Special Fire Fighting Procedures **Section 6 - Accidental Release Measures** Spill and Leak Small leaks-mop up, wipe up, or soak up immediately. Large spills-contain material and ventilate area. Do not dump into sewers, on the ground, or into any Requirements **Section 7 - Handling and Special Storage** Handling and Keep containers closed when not in use. Store in a cool place with adequate ventalation. Storage location should be constructed for containment and Special Storage dilution/neutralization of spills. Additional Storage Requirements **Section 8 - Exposure Controls and Personal Protection** Eye Protection Wear approved eye protection to safeguard against potential eye contact, irritation. Skin Protection Wear gloves to avoid prolonged contact with skin. N/A Comments **Section 9 - Physical and Chemical Properties** Physical State Liquid-Cream **Evaporation Rate** Like Water Light Brown Cream - Slight Solvent Odor **Boiling Point** 220 F Odor and Appearance 0.9916 Not Determined Specific Gravity Freezing Point 6.5 Vapour Pressure Not Determined Vapour Densisty >1 Density (g/ml) Not Determined Section 10 - Stability and Reactivity Stability Material is Stable Material is NOT Stable Incompatibility Strong Oxidizing Material Hazardous Decomposition Products Thermal decomposition may yield carbon monoxide and/or carbon dioxide Hazardous Polymerization May Occur Will NOT Occur



## Material Safety Data Sheet Luxcare Paint Protector & Renewer



### **Section 11 - Toxicological Information**

Acute Over Exposure Effects		Not Determined
Chronic Over Exposure Effects		Not Determined
Eye Contact May cause irritation		n.
Skin Contact May cause irritation		n, avoid prolonged contact with skin.
If Inhaled N/A		
		e to gastrointestinal tissue which may include pain, vomiting, nausea, abdominal tenderness, burns of mouth, difficulty swallowing, blood in feces, and ulceration.

### **Section 12 - Ecological Information**

### **Section 13 - Disposal Considerations**

Dispose in accordance with local, state, and federal regulations.

### **Section 14 - Transportation Information**

Ship as per DOT requirements in 49 CFR. Ship in accordance with local, state, and federal regulations.

### **Section 15 - Regulatory Information**

No.	Chemical Identity	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22
2	Solvent Naphtha (Petroleum) Medium Aliphatic																						
4																							
5	Organic Emulsion																						
6	Poly (Dimethylsiloxane)																						

(1) EHS-RQ (2) CERCLA (3) RQ (4) CAA 122r (5) TPQ (6) FIFRA (7) RCRA Code (8) Cal-CARC (9) Priority Polutant (10) Cal-Well Monitoring (11) SARA 313 (12) SARA 302 (13) MCL (14) Cal-HOT SPOT (15) Cal-Drinking Water (16) Cal-Toxic Air (17) NESHAP (18) Cal-Prop 65 (19) DOT Inhalation (20) Director's List (21) EPA Air (22) Cal-Reg Pest. An "X" in Column 11 indicates that this product contains a toxic chemical subject to the reporting requirements of Section 313 of EPCRA (40 CFR 372)

MSDS No.	4	Date Reviewed	4/15/2007	Prepared By	Ronnie L. Meadows			
Trade Name	Luxcare Paint Protector & Renewer	Supersedes	5/23/2002	Phone Number	(210) 564-3200			

TLV - Threshold Limit Value. An estimate of the average safe airborne concentration of a substance in representative conditions under which it is believed that nearly all workers may be repeatedly exposed day after day without adverse effect. TLVs are published annually by the ACGIH (American Conference of Governmental Industrial Hygienists). PEL - Permissible Exposure Limit. The OSHA limit of employee exposure to chemicals; found primarily in 29 CFR 1910.1000.

STEL - Short Term Exposure Limit. The maximum concentration for a continuous 15-minute exposure period.

IDLH - Immediately Dangerous to Life and Health. The concentration of a airborne chemical which may cause irreversible health effects or death. Ceiling - The maximum allowable concentration to which an employee may be exposed.

We believe the statements, technical information and recommendations contained herein are reliable. However, the data is provided without warranty, expressed or implied. It is the users responsibility both to determine safe conditions for use of this product and assume loss, damage or expense, direct or consequential, arising from its use. Before using this product, read label. The information contained in this publication is intended for general information purposes only. This publication is not a substitute for review of the applicable government regulations and standards, and should not be construed as legal advice or opinion. Readers with specific questions should refer to the cited references.