

SAFETY DATA SHEET



Date Prepared : 04/14/2015

MSDS No : R/A Rustproofing

ResistAll Rustproofing

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: ResistAll Rustproofing

GENERAL USE: Protection of automotive metal surfaces from the effects of environmental exposure.

GENERIC NAME: Mixture

MANUFACTURER

Cal-Tex Protective Coatings, Inc.

7455 Natural Bridge Caverns Rd.

Schertz, TX 78154-3210

Customer Service: 210-564-3200

24 HR. EMERGENCY TELEPHONE NUMBERS

INFOTRAC (US Transportation): 800-535-5053

Poison Control Center (Medical): 877-800-5553

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Target Organ Toxicity (Repeated exposure), Category 1

Aspiration Hazard, Category 1

Physical:

Flammable Liquids, Category 3

GHS LABEL



Flame



Health
hazard

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

6361MNCH: Causes damage to organs through prolonged or repeated exposure

PRECAUTIONARY STATEMENT(S)

Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P270: Do not eat, drink or smoke when using this product.

P241: Use explosion-proof [electrical/ventilating/lighting/...] equipment.

P242: Use non-sparking tools.

178906Z7: Take precautionary measures against static discharge.

26988X51: Wash face, hands and any exposed skin thoroughly after handling.

66683DSD: Wear protective gloves/ eye protection/ face protection

ResistAll Rustproofing

P233: Keep container tightly closed.

Response:

P370: In case of fire:.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/...

P331: Do NOT induce vomiting.

P314: Get medical advice/attention if you feel unwell.

Storage:

P405: Store locked up.

P403+P235: Store in a well-ventilated place. Keep cool.

Disposal:

3912LZZT: Dispose of contents/container in accordance with local, state and federal regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Petroleum Distillates, Hydrotreated Light	30 - 40	64742-47-8
Mineral Spirits (with <0.1% Benzene)	10 - 20	8052-41-3

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN: Wash affected area with soap and water. If irritation develops and persists, get medical attention. Wash contaminated clothing before reuse.

INGESTION: DO NOT induce vomiting, get medical attention/advice if you feel unwell.

INHALATION: Move to fresh air. Call a physician if symptoms develop or persist.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: May include redness, swelling, pain, tearing, and blurred or hazy vision.

SKIN: May include localized redness, swelling, and itching.

INGESTION: May include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

INHALATION: May include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

NOTES TO PHYSICIAN: Ensure that medical personnel are aware of the materials involved and take precautions to protect themselves.

5. FIRE FIGHTING MEASURES

GENERAL HAZARD: Heat from nearby fire may evaporate water from the product, leaving combustible components.

EXTINGUISHING MEDIA: Use water spray, alcohol-resistant foam, dry chemical, carbon dioxide (CO₂)

HAZARDOUS COMBUSTION PRODUCTS: Burning may produce toxic vapors, including carbon monoxide.

EXPLOSION HAZARDS: Vapors may form explosive mixtures with air.

FIRE FIGHTING PROCEDURES: Avoid flow of material into drains. Use a water spray to cool fire-exposed containers. Do not enter any enclosed or confined space without proper PPE.

FIRE FIGHTING EQUIPMENT: Firefighters should use standard protective equipment including flame retardant coat, helmet with

ResistAll Rustproofing

face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Soak up with sawdust, sand, oil dry, paper towel or other absorbent material

LARGE SPILL: Confine spill by diking or impoundment. Clean up spill by absorbing with an inert material such as sand, soil, sawdust, oil dry or vermiculite. Sweep up absorbant and dispose according to regulatory requirements. Ventilate area to avoid breathing vapors or dust.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Keep spills and cleaning runoffs out of storm sewers and open bodies of water.

LAND SPILL: Prevent further leakage or spillage if safe to do so.

GENERAL PROCEDURES: Remove sources of heat or ignition. Stop spill/leak at source if possible without risk.

SPECIAL PROTECTIVE EQUIPMENT: Wear appropriate personal protective equipment.

COMMENTS: Keep unnecessary personnel away, isolate spill ro leak area, beware of slippery floors and surfaces

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep out of reach of children. Keep container closed when not in use to prevent drying out.

HANDLING: Keep away from heat, sparks, flame or any other ignition source.

STORAGE: Store in original container protected from direct sunlight in a dry, cool, well-ventilated area and away from food and drink.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
Chemical Name	EXPOSURE LIMITS			
	Type		ppm	mg/m ³
Petroleum Distillates, Hydrotreated Light	OSHA PEL	TWA	[1]	5 [1]
	ACGIH TLV	TWA	200	5
		STEL	[2]	10 [2]
Mineral Spirits (with <0.1% Benzene)	OSHA PEL	TWA	500	2900
	ACGIH TLV	TWA	100	

Footnotes:
 1. Mist
 2. Inhalable fraction

ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: If contact is likely, safety glasses with side shields are recommended.

SKIN: Suitable chemical protective gloves should be worn when the potential exists for prolonged or repeated skin exposure. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Nitrile gloves are recommended.

RESPIRATORY: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 or applicable federal/state

ResistAll Rustproofing

requirements must be followed whenever workplace conditions warrant respirator use. NIOSH's "Respirator Decision Logic" may be useful in determining the suitability of various types of respirators.

PROTECTIVE CLOTHING: Wear suitable protective clothing. Wear appropriate chemical resistant clothing if applicable.

WORK HYGIENIC PRACTICES: Handle in accordance with good industrial hygiene and safety practice.

OTHER USE PRECAUTIONS: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking and smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Viscous liquid

ODOR: Slight solvent odor

ODOR THRESHOLD: Not Available

COLOR: Off white

pH: 8.2

FLASH POINT AND METHOD: 77°C (171°F)

FLAMMABLE LIMITS: Not Available to Not Available

AUTOIGNITION TEMPERATURE: Not Available

VAPOR PRESSURE: Not Available

VAPOR DENSITY: Not Available

BOILING POINT: Not Available

MELTING POINT: Not Available

THERMAL DECOMPOSITION: Not Available

SOLUBILITY IN WATER: Dispersible

EVAPORATION RATE: Not Available

SPECIFIC GRAVITY: 1.01

VISCOSITY: Not Established

10. STABILITY AND REACTIVITY

REACTIVITY: This product is stable and non-reactive under normal conditions of use, storage and transport.

HAZARDOUS POLYMERIZATION: Will not occur.

STABILITY: Stable under normal storage and handling conditions.

CONDITIONS TO AVOID: Keep away from extreme heat, strong acids and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Upon decomposition this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

INCOMPATIBLE MATERIALS: Strong oxidizers.

11. TOXICOLOGICAL INFORMATION

RESPIRATORY OR SKIN SENSITISATION: This product is not expected to cause skin sensitization.

CARCINOGENICITY

ResistAll Rustproofing

NOTES: The ingredients of this product are not classed as carcinogenic by ACGIH, IARC, OSHA or NTP.

REPRODUCTIVE TOXICITY: Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals.

STOT-SINGLE EXPOSURE: Not classified.

STOT-REPEATED EXPOSURE: Prolonged or repeated contact with product may cause drying or chapping of the skin.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

BIOACCUMULATION/ACCUMULATION: Product is not expected to bioaccumulate.

GENERAL COMMENTS: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Refer to all federal, state and local regulations prior to disposal of container and unused contents by reuse, recycle or disposal. Disposal should be in accordance with applicable regional, national and local laws and regulations. Send to a licensed/permitted waste desposer, recycler, reclaimer or incinerator.

EMPTY CONTAINER: Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

RCRA/EPA WASTE INFORMATION: Wastes of this product must be tested using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: In containers of 119 gallons or less, this product ships as "Non-Regulated" per US DOT exemption for Combustible Liquids (49 CFR 173.150).

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: None

FIRE: No **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** No **CHRONIC:** No

313 REPORTABLE INGREDIENTS: None listed

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: Not Regulated

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: Not listed


TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA REGULATORY: All intentional ingredients are listed in the TSCA Inventory or comply with TSCA Polymer Exemption criteria in accordance with 40 CFR 723.

ResistAll Rustproofing

CLEAN AIR ACT**40 CFR PART 68---RISK MANAGEMENT FOR CHEMICAL ACCIDENT RELEASE PREVENTION:** Not Regulated**CALIFORNIA PROPOSITION 65:** This product does not contain any substances which are known to the state of California to cause cancer, birth defects, or other reproductive effects.**16. OTHER INFORMATION****PREPARED BY:** Cal-Tex Compliance Office **Date Prepared:** 04/14/2015**HMIS RATING**

HEALTH	<input type="text"/>	2
FLAMMABILITY	<input type="text"/>	2
PHYSICAL HAZARD	<input type="text"/>	0
PERSONAL PROTECTION	<input type="text"/>	B

NFPA CODES

MANUFACTURER DISCLAIMER: We believe the statements, technical information and recommendations contained herein are reliable. However, the data is provided without warranty, expressed or implied. It is the users responsibility both to determine safe conditions for use of this product and assume loss, damage or expense, direct or consequential, arising from its use. Before using this product, read label. The information contained in this publication is intended for general information purposes only. This publication is not a substitute for review of the applicable government regulations and standards, and should not be construed as legal advice or opinion. Readers with specific questions should refer to the cited references.